



*YOUR LEADER IN METALWORKING FLUIDS, LUBRICANTS, CLEANERS, CHEMICALS, AND MIL-SPEC PRODUCTS*

## **DEOLUBE S-TYPE LUBRICATING OILS**

Deolube S-Type is our premium line of rust and oxidation-inhibited lubrication and general-duty machine oils. Deolube S is formulated with premium base stocks and a carefully balanced package of anti-rust, anti-oxidation, anti-foam, and demulsibility additives. Deolube S gives excellent long-life service under the most demanding conditions. No conventional oil of this class gives better service than Deolube S.

	<b>32-S</b>	<b>46-S</b>	<b>68-S</b>	<b>100-S</b>	<b>150-S</b>	<b>220-S</b>	<b>320-S</b>	<b>460-S</b>
Specific Gravity	.867	.873	.877	.881	.887	.890	.897	.900
Pour Point, °C (°F)	-7 (20)	-7 (20)	-7 (20)	-7 (20)	-4 (25)	-4 (25)	-4 (25)	-4 (25)
Flash Point, °C (°F)	204 (400)	204 (400)	204 (400)	210 (410)	227 (440)	227 (440)	238 (460)	271 (520)
Viscosity								
cSt at 40 °C	30.4	43.7	64.6	95	157.5	230	335	437
cSt at 100 °C	5.1	6.5	8.4	11.4	14.7	19.3	24.7	31.8
SUS at 100 °F	158	228	335	495	840	1245	1815	2338
SUS at 210 °F	44	48.8	55	65.5	80.5	99.1	123	153
Viscosity Index	95	95	95	95	95	95	95	95
ISO VG	32	46	68	100	150	220	320	460
Color, ASTM D 1500	1.5	2.0	2.5	2.5	4.5	5.0	6.0	6.5
Neut. No.	0.20	.025	0.30	0.30	1.2	1.2	1.2	1.2
Rust Protection, ASTM D 665 A & B	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Demulsibility, ASTM D 1401, min to 0 ml emulsion at 54°C (130°F) after 30 minutes	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass

W.S. DODGE OIL  
 3710 FRUITLAND AVE. MAYWOOD, CA 90270  
 (323) 583-3478 F (323) 583-0950  
[www.wsdodgeoil.com](http://www.wsdodgeoil.com)